

INSTRUCTIONS FOR KQ-330 & KQ-440 SHAKER

It is very important to read these instructions for installation of your KQ-330 & KQ-440 shaker.

1. Remove bolt located -it rear of tub. This bolt is positioned between both supporting springs.
2. It is recommended that your shaker be bolted to the ground, as well as the timer stand, guiding holes have been made for your convenience.
3. Ceramic media has been supplied. Place 6 gallon pail under drain pipe located on the right hand side of the shaker. Fill with 4 gallons of a preferred cleaning solution and 1/2 gallon of water to keep residual sludge from hardening at bottom of pail.
4. Place pump in the pail, base in first. Plug in the outlet located to the right side of the shaker.
5. Plug in the unit to any 115V AC, single phase outlet.

Your Shaker is now ready for operation. Set timer to desired setting, unit will automatically him on.

FOR CLEANING PLEASE REFER TO THE FOLLOWING:

1. Remove pump from pail
- 2. Dispose of solvent and residual sludge according to local and E.P.A. approved methods.**
3. Refill pail as recommended in step three of installation instructions.

WARRANTY

This equipment is warranted by Kar Industries Corp. for one year from date of purchase for defects in workmanship or materials under use. All parts and repairs under warranty must be shipped prepaid to the Miami, Florida Plant. The warranty does not apply to damages resulting from accidents, misuse or alterations.

Should you have any questions please call our technical support line at: (305)594-0790